



Torque wrench MANOSKOP®

730R Quick




Product no. **96504004**
GTIN **4018754311361**
Model **730R/4 QUICK**



Label.

Torque wrench MANOSKOP® 730R Quick 8-40N·m 3/8" L. 285mm



Product highlights.



Rapid adjustment.

Easy and quick adjustment of the torque is carried out by an easy-to-operate clamping lever in the handle. The scale can be moved quickly and safely with an ergonomically shaped, non-slip adjustment element with thumb recess.



Adjustment does not require disassembly.

Quick adjustment from outside, no disassembly of the torque wrench required, with 2 adjustment points for the maximum & minimum values.



Technologies and features.



Low-wear bending beam system

Our torque wrench is equipped with a low-wear release system with a bending beam. Unlike conventional torque wrenches with coiled springs, the bending beam is not subjected to any load until the tool is in operation, which means that resetting to '0' is not necessary after use.




2-component handle

Our 2-component handle is non-slip and ergonomically designed. It is resistant to the most common oils, greases, fuels, brake fluids, and Skydrol. The arrow markings on the handle indicate the direction of operation.



DIN EN ISO 6789-2


Our torque wrenches and torque screwdrivers are professionally calibrated in accordance with DIN EN ISO 6789-2 and delivered with a corresponding calibration certificate. We also calibrate angle-controlled torque wrenches in accordance with VDI 2648-2. This ensures the accuracy and traceability of our tools.



QuickSelect

Lightning-fast target value setting: Unlock the adjustment knob, set the value, and lock the knob again.

Technical drawing.



Technical attributes.

Size	4
Anzeigeabweichung	$\pm 4 \%$
Tool holder size [internal square]	9 x 12 mm
Measuring range N·m	8-40 N·m
MA N·m	8 N·m
Nominal value N·m	40 N·m
Scale division N·m	1 N·m
External square drive (inch)	3/8
Length mm (L)	285 mm
b1	55 mm
b2	33 mm
Height mm (h)	55 mm
DIN	DIN EN ISO 6789-2:2017
LF	200,8 mm
SF	17,5 mm

Logistics data.

Product no.	96504004
GTIN	4018754311361
Weight (g)	642 g
Volume (packaged, dm3)	0.862125 dm3
Packing standard	1
WEEE/ElektroG	nicht ear-pflichtig
Customs tariff no.	82041100
Country of origin AWR	GERMANY
Region of origin	Nordrhein-Westfalen
Depth mm (IFS)	285
Width mm (IFS)	55
Height mm (IFS)	55
Weight (gross, kg)	0,624
Weight PAP (kg)	0,000
Weight PVC (kg)	0,066
Length (packaged, mm)	285
Width (packaged, mm)	55
Height (packaging, mm)	55

Parts list.



50184004
Torque wrench service
MANOSKOP® (N·m)

GTIN.



Images.



STAHLWILLE Eduard Wille GmbH

Lindenallee 27 · 42349 Wuppertal · Germany · Phone: +49 202 4791-0

info@stahlwille.de · www.stahlwille.com

© STAHLWILLE Eduard Wille GmbH, Wuppertal