



Torque wrench service MANOSKOP® with fine-tooth ratchet

730NR




Product no. **96503110**
GTIN **4018754229383**
Model **730NR / 10FK**



Label.

Torque wrench service MANOSKOP® 730NR 15-75ft·lb 1/2 L. 420mm

Product highlights.



Reliable handling.

The haptic feedback and a clearly audible 'click' as a dual stop signal from the mechanical trigger reliably indicate that the target value has been reached.



Precise torque in an instant.

The main and fine scale with fixed values enables quick, easy, and precise adjustment via the adjustment wheel - for maximum reliability in every application.



Clear fine adjustment.

The user-friendly and easy-to-read dual scale in N·m/ft·lb with main and fine scales allows for precise and easy torque adjustment for reliable and accurate application.



Maximum safety.

The clicking mechanism of our torque wrench is insensitive to further and counter loads - even up to the maximum measuring range limit. This protects both the tool and the workpieces from damage and ensures precision and durability, even with higher forces.



Adjustment does not require disassembly.

Quick adjustment from outside, no disassembly of the torque wrench required, with 2 adjustment points for the maximum & minimum values.

Technologies and features.



Low-wear bending beam system

Our torque wrench is equipped with a low-wear release system with a bending beam. Unlike conventional torque wrenches with coiled springs, the bending beam is not subjected to any load until the tool is in operation, which means that resetting to '0' is not necessary after use.




2-component handle

Our 2-component handle is non-slip and ergonomically designed. It is resistant to the most common oils, greases, fuels, brake fluids, and Skydrol. The arrow markings on the handle indicate the direction of operation.



DIN EN ISO 6789-2


Our torque wrenches and torque screwdrivers are professionally calibrated in accordance with DIN EN ISO 6789-2 and delivered with a corresponding calibration certificate. We also calibrate angle-controlled torque wrenches in accordance with VDI 2648-2. This ensures the accuracy and traceability of our tools.



QuickSelect

Lightning-fast target value setting: Unlock the adjustment knob, set the value, and lock the knob again.

Technical drawing.



Technical attributes.

Size	10 FK
Anzeigeabweichung	± 4 %
Measuring range N·m	20-100 N·m
Measuring range ft·lb	15-75 ft·lb
MA N·m	20 N·m
Nominal value N·m	100 N·m
Scale division N·m	10 N·m
Scale division ft·lb	2,5 ft·lb
Fine scale division	0,5 N·m
External square drive (inch)	1/2
Length mm (L)	420 mm
b1	28 mm
b2	33 mm
Height mm (h1)	23 mm
Height mm (h2)	24 mm
DIN	DIN EN ISO 6789-2:2017
LF	336,5 mm
Weight with box	1934 g

Logistics data.

Product no.	96503110
GTIN	4018754229383
Weight (g)	1146 g
Volume (packaged, dm3)	3.724 dm3
Packing standard	1
WEEE/ElektroG	nicht ear-pflichtig
Customs tariff no.	82041100
Country of origin AWR	GERMANY
Region of origin	Nordrhein-Westfalen
Depth mm (IFS)	560
Width mm (IFS)	95
Height mm (IFS)	70
Weight (gross, kg)	1,745
Weight PAP (kg)	0,095
Weight PVC (kg)	0,000
Length (packaged, mm)	560
Width (packaged, mm)	95
Height (packaging, mm)	70

Parts list.



81370002

Plastic box, empty

GTIN.



STAHLWILLE Eduard Wille GmbH

Lindenallee 27 · 42349 Wuppertal · Germany · Phone: +49 202 4791-0

info@stahlwille.de · www.stahlwille.com

© STAHLWILLE Eduard Wille GmbH, Wuppertal