



## Torque wrench service MANOSKOP® (N·m)

### 730 Quick

Product no. 50184001  
GTIN 4018754359035  
Model 730/2-1 QUICK



#### Label.

Torque wrench service MANOSKOP® (N·m) 730 Quick 2-10N·m 9 x 12 mm L. 179mm



## Product highlights.



#### Rapid adjustment.

Easy and quick adjustment of the torque is carried out by an easy-to-operate clamping lever in the handle. The scale can be moved quickly and safely with an ergonomically shaped, non-slip adjustment element with thumb recess.



#### Adjustment does not require disassembly.

Quick adjustment from outside, no disassembly of the torque wrench required, with 2 adjustment points for the maximum & minimum values.



## Technologies and features.



### Low-wear bending beam system

Our torque wrench is equipped with a low-wear release system with a bending beam. Unlike conventional torque wrenches with coiled springs, the bending beam is not subjected to any load until the tool is in operation, which means that resetting to '0' is not necessary after use.




### 2-component handle

Our 2-component handle is non-slip and ergonomically designed. It is resistant to the most common oils, greases, fuels, brake fluids, and Skydrol. The arrow markings on the handle indicate the direction of operation.



### DIN EN ISO 6789-2


Our torque wrenches and torque screwdrivers are professionally calibrated in accordance with DIN EN ISO 6789-2 and delivered with a corresponding calibration certificate. We also calibrate angle-controlled torque wrenches in accordance with VDI 2648-2. This ensures the accuracy and traceability of our tools.



### QuickSelect

Lightning-fast target value setting: Unlock the adjustment knob, set the value, and lock the knob again.

## Technical drawing.



## Technical attributes.

|                                    |            |
|------------------------------------|------------|
| Size                               | 2-1        |
| Anzeigeabweichung                  | $\pm 4 \%$ |
| Tool holder size [internal square] | 9 x 12 mm  |
| Measuring range N·m                | 2-10 N·m   |
| MA N·m                             | 2 N·m      |
| Nominal value N·m                  | 10 N·m     |
| Scale division N·m                 | 0,25 N·m   |
| Length mm (L)                      | 179 mm     |
| Width mm (b)                       | 27,5 mm    |
| Height mm (h)                      | 23,6 mm    |
| LF                                 | 157,2 mm   |
| SF                                 | 17,5 mm    |

## Logistics data.

|                                     |                         |
|-------------------------------------|-------------------------|
| Product no.                         | 50184001                |
| GTIN                                | 4018754359035           |
| Weight (g)                          | 315 g                   |
| Volume (packaged, dm <sup>3</sup> ) | 0.75625 dm <sup>3</sup> |
| Packing standard                    | 1                       |
| WEEE/ElektroG                       | nicht ear-pflichtig     |
| Customs tariff no.                  | 82041100                |
| Country of origin AWR               | GERMANY                 |
| Region of origin                    | Nordrhein-Westfalen     |
| Depth mm (IFS)                      | 182                     |
| Width mm (IFS)                      | 45                      |
| Height mm (IFS)                     | 30                      |
| Weight (gross, kg)                  | 0,400                   |
| Weight PAP (kg)                     | 0,000                   |
| Weight PVC (kg)                     | 0,096                   |
| Length (packaged, mm)               | 250                     |
| Width (packaged, mm)                | 55                      |
| Height (packaging, mm)              | 55                      |

GTIN.



**STAHLWILLE Eduard Wille GmbH**

Lindenallee 27 · 42349 Wuppertal · Germany · Phone: +49 202 4791-0

[info@stahlwille.de](mailto:info@stahlwille.de) · [www.stahlwille.com](http://www.stahlwille.com)

© STAHLWILLE Eduard Wille GmbH, Wuppertal