



Torque wrench MANOSKOP®

721 Quick



Product no. **50204030**
GTIN **4018754268948**
Model **721/30 QUICK**



Label.

Torque wrench MANOSKOP® 721 Quick 60-300N·m 1/2" L. 553mm

Product highlights.



Rapid adjustment.


Easy and quick adjustment of the torque is carried out by an easy-to-operate clamping lever in the handle. The scale can be moved quickly and safely with an ergonomically shaped, non-slip adjustment element with thumb recess.



Adjustment does not require disassembly.

Quick adjustment from outside, no disassembly of the torque wrench required, with 2 adjustment points for the maximum & minimum values.

Technologies and features.



Low-wear bending beam system

Our torque wrench is equipped with a low-wear release system with a bending beam. Unlike conventional torque wrenches with coiled springs, the bending beam is not subjected to any load until the tool is in operation, which means that resetting to '0' is not necessary after use.




2-component handle

Our 2-component handle is non-slip and ergonomically designed. It is resistant to the most common oils, greases, fuels, brake fluids, and Skydrol. The arrow markings on the handle indicate the direction of operation.



DIN EN ISO 6789-2


Our torque wrenches and torque screwdrivers are professionally calibrated in accordance with DIN EN ISO 6789-2 and delivered with a corresponding calibration certificate. We also calibrate angle-controlled torque wrenches in accordance with VDI 2648-2. This ensures the accuracy and traceability of our tools.



QuickSelect

Lightning-fast target value setting: Unlock the adjustment knob, set the value, and lock the knob again.

Technical drawing.



Technical attributes.

Size	30
Anzeigeabweichung	± 4 %
Measuring range N·m	60-300 N·m
Measuring range ft·lb	50-220 ft·lb
MA N·m	60 N·m
Nominal value N·m	300 N·m
Scale division N·m	10 N·m
Scale division ft·lb	10 ft·lb
External square drive (inch)	1/2
Length mm (L)	553 mm
b1	28 mm
b2	44 mm
Height mm (h1)	23 mm
Number of teeth	36
DIN	DIN EN ISO 6789-2:2017
LF	486 mm

Logistics data.

Product no.	50204030
GTIN	4018754268948
Weight (g)	1646 g
Volume (packaged, dm3)	1.7545 dm3
Packing standard	1
WEEE/ElektroG	nicht ear-pflichtig
Customs tariff no.	82041100
Country of origin AWR	GERMANY
Region of origin	Nordrhein-Westfalen
Depth mm (IFS)	555
Width mm (IFS)	46
Height mm (IFS)	30
Weight (gross, kg)	1,812
Weight PAP (kg)	0,000
Weight PVC (kg)	0,118
Length (packaged, mm)	580
Width (packaged, mm)	55
Height (packaging, mm)	55

GTIN.



Accessories (for).



81370003
Plastic box, empty

Spare part(s), spare part(s) for.



59191030

Spare part set for
ratchet

Images.



STAHLWILLE Eduard Wille GmbH

Lindenallee 27 · 42349 Wuppertal · Germany · Phone: +49 202 4791-0

info@stahlwille.de · www.stahlwille.com

© STAHLWILLE Eduard Wille GmbH, Wuppertal